



Plastic Drill/Tool Cassette RoseBox

High-quality plastic cassettes in modern design. Ideal for all kinds of drill bit sets, precision tools, shank tools, special tool sets and spare parts

Material

- cover and base in ABS
- insert, closure and hanger in Polypropylene (PP)
- hinges in Polyamide (PA)

Product Range

- bases in light gray
- cover, closure and hanger in dark gray
- insert and length 'stop' in black
- additional colors and color combinations on request
- version with clear window in cover on request

Product features RoseBox

- modular concept - cassettes can be combined with individual foam inserts or vacuum formed inserts
- intergral secure locking mechanism to prevent unintended opening on impact
- adjustable and flexible length stop for tools
- modern design
- functional and user-friendly
- universal application
- resilient and stable
- excellent for stacking and storage
- space for labelling on cover and base
- optional with intergrated clear window in cover for optimum product presentation

| Article | Number of holding devices | Suitable for | Index design | Standardization | Outer length | Outer width | Outer depth | Packaging Unit |
|---------|---------------------------|------------------------|--|----------------------------|--------------|-------------|-------------|----------------|
| 1A 87 | 30 | Bits+Magnetic holder | 30 Bits+Magnetic holder Ø 10mm | | 120 | 87 | 36 | 90 |
| 2B 11 | 3 | Sheet and tube drills | 3-14/8-20/16-30.5 | | 146 | 100 | 42 | 54 |
| 3A 68 | 3 | Sheet and tube drills | 3-14/8-20/16-30.5+cutting compound | | 172 | 115 | 42 | 65 |
| 3A 33 | 15 | Spiral point taps | each machine tap M3-M12+each 1 core hole drill 2.5/3.3/4.2/5/ 6.8/8.5/10.2+1 tapwrench | DIN 352 | 172 | 115 | 42 | 65 |
| 2B 24 | 4 | Deburring countersinks | 2-5/5-10/10-15/15-20 | | 146 | 100 | 42 | 54 |
| 3A 60 | 5 | Deburring countersinks | 2-5/5-10/10-15/15-20/20-25 | | 172 | 115 | 42 | 65 |
| 2B 58 | 6 | Flat counterbores | M3/M4/M5/M6/M8/M10 | DIN 373 | 146 | 100 | 42 | 54 |
| 2B 22 | 10 | Rotary burrs | Shank-diam. 6mm; 10 diff. head diameters | | 146 | 100 | 42 | 54 |
| 2B 85 | 5 | Rotary burrs | Shank-diam. 6mm; 5 diff. head diameters, length 71mm | | 146 | 100 | 42 | 54 |
| 2B 90 | 10 | Rotary burrs | Shank-diam. 6mm; 10 diff. head diameters, length 71mm | | 146 | 100 | 42 | 54 |
| 1A 88 | 7 | Threading dies | M3-M12 | | 120 | 87 | 36 | 90 |
| 4A 08 | 7 | SDS Drills | 5.0x110/6.0x110/6.0x160/8.0x110/8.0x160/10.0x160/12.0x160 (SDS-Plus-Shaft) | | 200 | 115 | 42 | 60 |
| 4B 54 | 28 | Hand taps | 1 set (3) each hand taps M3-M12+each 1 drill 2.5/3.3/4.2/5/ 6.8/8.5/10.2 | DIN 352 | 200 | 115 | 58 | 38 |
| 4B 107 | 21 | Hand taps | 1/8. 3/16. 1/4. 5/16. 3/8. 7/16. 1/2 BSW // 3/16-1/2 UNC. UNF. BSF | ISO 529 | 200 | 115 | 58 | 38 |
| 3A 20 | 21 | Hand taps | 1 set (3) each hand taps M3/M4/M5/M6/M8/M10/M12 | DIN 352 | 172 | 115 | 42 | 65 |
| 4B 41 | 28 | Hand taps | 1 set (3) each hand taps M3-M12+each 1 drill 2.5/3.3/4.2/5/ 6.8/8.5/10.2 | ISO 529 | 200 | 115 | 58 | 38 |
| 3A 43 | 21 | Hand taps | 1 set (3) each hand taps M3/M4/M5/M6/M8/M10/M12 | ISO 529 | 172 | 115 | 42 | 65 |
| 2B 103 | 13 | HSS drills | 1/16"-1/4"x1/64" | ANSI Jobber Length/DIN 338 | 146 | 100 | 42 | 54 |
| 2B 106 | 11 | HSS drills | 1.0-6.0x0.5mm | DIN 338 | 146 | 100 | 42 | 54 |
| 3A 06 | 21 | HSS drills | 1/16"-3/8"x1/64" | DIN 338 | 172 | 115 | 42 | 65 |
| 3A 117 | 19 | HSS drills | 1.0-10.0x0.5mm | DIN 338 | 172 | 115 | 42 | 65 |
| 4A 05 | 15 | HSS drills | 1/16"-1/2"x1/32" | DIN 338 | 200 | 115 | 42 | 60 |
| 4B 03 | 25 | HSS drills | 1.0-13.0x0.5mm | DIN 338 | 200 | 115 | 58 | 38 |
| 4B 07 | 29 | HSS drills | 1/16"-1/2"x1/64" | DIN 338 | 200 | 115 | 58 | 38 |
| 4B 09 | 24 | HSS drills | 1.0-10.5x0.5mm+core hole drills 3.3/4.2/6.8/10.2 | DIN 338 | 200 | 115 | 58 | 38 |
| 4B 36 | 51 | HSS drills | 1.0-6.0x0.1mm | DIN 338 | 200 | 115 | 58 | 38 |
| 5B 72 | 41 | HSS drills | 6.0-10.0x0.1mm | DIN 338 | 200 | 167 | 65 | 24 |
| 4B 36/8 | 50 | HSS drills | 1.0-5.9x0.1mm | DIN 338 | 200 | 115 | 58 | 38 |
| 4B 95 | 29 | HSS drills | 1.0-13.0x0.5mm+core hole drills 3.3/4.2/6.8/10.2 | DIN 338 | 200 | 115 | 58 | 38 |
| 4B 105 | 26 | HSS drills | Letter Gauge Drills A-Z (Jobber Length) (ASME B94.11 M) | | 200 | 115 | 58 | 38 |
| 5B 104 | 60 | HSS drills | Wire Gauge Drills 1-60 (ASME B94.11 M) | | 200 | 167 | 65 | 24 |
| 3A 83 | 19 | HSS short drills | 1.0-10.0x0.5mm | DIN 1897 | 172 | 115 | 42 | 65 |
| 2B 12 | 6 | Countersinks | 6.3/8.3/10.4/12.4/16.5/20.5 | DIN 335-C | 146 | 100 | 42 | 54 |

| Article | Number of holding devices | Suitable for | Index design | Standardization | Outer length | Outer width | Outer depth | Packaging Unit |
|---------|---------------------------|---|--|-----------------|--------------|-------------|-------------|----------------|
| 2B 13 | 6 | Countersinks | 6.8/10/11.5/15/19 | DIN 335-C | 146 | 100 | 42 | 54 |
| 2B 14 | 6 | Countersinks | 6.3/8.3/10.4/12.4/16.5/20.5 long series | DIN 335-C | 146 | 100 | 42 | 54 |
| 2B 69 | 7 | Countersinks | 6.8/10/11.5/15/19/25 | DIN 335-C | 146 | 100 | 42 | 54 |
| 2B 78 | 5 | Countersinks | 6.3/10.4/16.5/20.5/25 | DIN 335-C | 146 | 100 | 42 | 54 |
| 4A 88 | 6 | Countersinks | 6.3-20.5 with extra long shank | DIN 335-C | 200 | 115 | 42 | 60 |
| 4B 62 | 17 | Countersinks | 4.3/5/6/6.3/7/8/8.3/10/10.4/11.5/12.4/15/16.5/19/20.5/23/25 | DIN 335-C | 200 | 115 | 58 | 38 |
| 3A 74 | 7 | Countersinks-Bits | 6 countersink bits 6.3/8.3/10.4/12.4/16.5/20.5 mm+bit holder Ø 1/4"; handle and cutting compound | DIN 3126 C 6.3 | 172 | 115 | 42 | 65 |
| 1A 80 | 6 | Combined tap and drills+magnetic holder | 6 combined tap and drill bits (M3-M12)+magnetic holder Ø 10mm | | 120 | 87 | 36 | 90 |
| 2B 35 | 7 | Machine taps | M3-M12 | DIN 371/376 | 146 | 100 | 42 | 54 |
| 3A 10 | 14 | Machine taps | each machine tap M3-M12+core hole drill 2.5/3.3/4.2/5/6.8/8.5/10.2 | DIN 371/376 | 172 | 115 | 42 | 65 |
| 3A 89 | 14 | Machine taps | each machine tap M3-M12+core hole drill 2.5/3.3/4.2/5/6.8/8.5/10.2 | ISO 529 | 172 | 115 | 42 | 65 |
| 3A 76 | 10/12 | Screwdriver | 5 screwdrivers+5 drills for M3-M18 (1/8"-3/4") or 6 screwdrivers+6 drills M3-M24 (1/8"-1") | | 172 | 115 | 42 | 65 |
| 2B 30 | 6 | Countersink bits HSS | 6.3/8.3/10.4/12.4/16.5/20.5+bit holder Ø 1/4" | DIN 3126 C 6.3 | 146 | 100 | 42 | 54 |
| 2B 21 | 3 | Step drills | 4-12/12-20/20-30 | | 146 | 100 | 42 | 54 |
| 2B 23 | 3 | Step drills | 4-12/4-20/6-30 | | 146 | 100 | 42 | 54 |
| 3A 71 | 3 | Step drills | 4-12/12-20/20-30+cutting compound | | 172 | 115 | 42 | 65 |
| 4A 37 | 6 | Pin punches | 2/3/4/5/6/8 | DIN 6450 C | 200 | 115 | 42 | 60 |
| 4A 29 | 7 | Masonry Drills | 4.0/5.0/6.0/6.0/8.0/10.0/12.0 | DIN 8039 | 200 | 115 | 42 | 60 |